



SHOWN WITH NAMUR ACCESSORY DRIVE. IDENTICAL MOUNTING PATTERNS AND SHAFT DRIVE EXIST ON BOTH SIDES, NAMUR ACCESSORIES MAY BE MOVED TO OPPOSITE SIDE.

MOUNTING PATTERNS: F10 AND 4.02x1.52 RECT

SHAFT: 36MM FEMALE DOUBLE SQUARE, 1.000 INCHES DEEP (MEASURED FROM MOUNTING SURFACE)

PORT SIZES AS ORDERED, 1/4 NPT STANDARD

DETAIL A
SCALE 2:7



REV.	DESCRIPTION	DATE	DRAWNBY
A	INITIAL	9-JUN-2014	JRH

STATUS	APPROVAL
Released	JRH 11 Jun 14

Except as shown, Dimensions are inches and standard Tolerances are:

Fractional +/- N/A
 Angular +/- N/A
 1 Decimal +/- N/A
 2 Decimal +/- N/A
 3 Decimal +/- N/A

DESCRIPTION	REVISION
	A

DO NOT SCALE DRAWING
PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF QTRCO, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF QTRCO, INC. IS PROHIBITED.

MATERIALS AS SPECIFIED BY PRODUCT LINE STANDARDS AND ORDERED OPTIONS. WEIGHT SHOWN WITH HEAVISET MATERIAL OPTIONS.

DWG. NO. Qx207SR-DIM-01	REVISION A
WEIGHT (Pounds): 51.429	SHEET 1 OF 1 1 of 1 if not shown
	SIZE A