



SHOWN WITH NAMUR ACCESSORY DRIVE. IDENTICAL MOUNTING PATTERNS AND SHAFT DRIVE EXIST ON BOTH SIDES. NAMUR ACCESSORIES MAY BE MOVED TO OPPOSITE SIDE.

MOUNTING PATTERNS: F16 AND 6.50x2.00 RECT

SHAFT: 55MM FEMALE DOUBLE SQUARE, 1.87 INCHES DEEP (MEASURED FROM MOUNTING SURFACE), 2 INCH BORE THRU SHAFT

PORT SIZES AS ORDERED, 1/4 NPT STANDARD

CoG MEASUREMENTS SHOWN WITH 16-INCH HANDWHEEL IN EXTENDED POSITION

SHOWN WITH 16-INCH DIAMETER ELEVATED HANDWHEEL. ACTUAL SIZE MAY VARY AS ORDERED.



REV.	DESCRIPTION	DATE	DRAWNBY
A	INITIAL	19-JAN-2015	JRH

STATUS	APPROVAL
Released	JRH 19 Jan 15

Except as shown, Dimensions are inches and standard Tolerances are:
 Fractional +/- N/A
 Angular +/- N/A
 1 Decimal +/- N/A
 2 Decimal +/- N/A
 3 Decimal +/- N/A

DESCRIPTION	REVISION
	A

DO NOT SCALE DRAWING
PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF QTRCO, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF QTRCO, INC. IS PROHIBITED.

MATERIALS AS SPECIFIED BY PRODUCT LINE STANDARDS AND ORDERED OPTIONS. WEIGHT SHOWN WITH HEAVISET MATERIAL OPTIONS.

DWG. NO.	REVISION	SIZE
Qx214SD-JR-DIM-01	A	A
WEIGHT (Pounds): 171.69	SHEET 1 OF 1 1 of 1 if not shown	